

# ADAPT™ RANGE



## OCTANE

The anterior and posterior ankle flexibility and lightweight design makes the Octane purpose built for workers that clock up big mileage on foot over rough terrain and those that need the flexibility to operate machinery. Built on the **ADAPT™** sole technology and **articulatedFIT™** upper the Octane is designed to improve adaption to rough surfaces and is combined with a lightweight design to assist in minimising fatigue and maximising performance.



**SIZES**  
**6-14**  
1/2 SIZES 6.5-10.5  
**HEIGHT**  
**160<sup>mm</sup>**  
**6<sup>7</sup>**  
**WEIGHT**  
**655<sup>g</sup>**

### COLOURS



### PERFORMANCE SYSTEMS

#### SYST-M®

Design philosophy that integrates series of technologies and design features to provide movement specific support and flexibility.

#### ADAPT™

Sole unit technology designed to maximise adaption to uneven terrain and reduce injury risks.

#### articulatedFIT™

Upper design system to allow the natural movement of the foot and ankle from heel strike to toe-off.

#### asymBEVEL™

Heel shaped to match the natural heel strike position during walking to maximise contact area and provide a smooth ride.

#### Ortholite®

Breathable memory foam insole that moulds to the foot providing a customised fit and helping to reduce in-shoe friction.

#### decoupleGROOVE™

Flex groove along the length of the sole to provide flexibility to allow a smooth transition from initial contact to foot flat and improve terrain adaption.

#### softboard™

Constructed on cushioned foam insole board for a smooth ride.

#### radiatorTECH™

Manufacturing technique used to improve the breathability of leather and lining materials.

#### endurelon™

Specifically compounded phylon midsole to improve cushioning rebound characteristics and durability.

#### WIDEcap

Wide anatomical shaped toecap to reduce rubbing and nerve impingement.

#### FITCHECK

Registered fitting guide printed on the insole to indicate the correct spacing between the end of the longest toe and the toecap.

### SAFETY SYSTEMS

#### COMPOSITE Toecap

Lightweight, metal-free, nonconductive, insulating and airport friendly safety toecap that complies with (AS/NZS 2210.3), (EN-ISO 20345) and (ASTM F2413-11) standards.

#### slipRESIST-C

Sole slip resistant to soap (SLS) on ceramic tiles and glyceryl on steel plate.

#### 300°C Heat Resistant

Nitrile rubber sole that is hard wearing and resistant to extreme heat.

#### fueloilRESIST

Sole resists breakdown to fuel oil.

#### ANTI-STATIC

Minimises static electricity build up for safety in volatile environments.

#### H<sub>2</sub>O RESISTANT

Footwear designed to shed water.

#### ScuffCAP

Improves durability in high wear zones.

#### LOWcatchsole

Low profile sole at the toe to reduce the risk of tripping.

#### REFLECTIVE

Upper contains retro-reflective material to improve visibility in low light conditions.

